

Lith-Ex Fire Extinguisher | Range

L2EX 500/1/2/6/9FC

- For use on lithium-ion battery fires
- Prevents re-ignition
- Quickly cools the excessive heat
- Non-toxic
- Environmentally-friendly
- 5-year warranty
- Annual servicing needed (excluding L2EX500) – call 01432 371170 to arrange



Effective use for fires on:



Specifications	L2EX9FC	L2EX6	L2EX2	L2EX1	L2EX500
Capacity	9ltr	6ltr	2ltr	1ltr	500ml
Fire rating	21A	13A	8A	5A	n/a
Medium	AVD*	AVD*	AVD*	AVD*	AVD*
Operating pressure	29 Bar	29 Bar	27 Bar	27 Bar	21 Bar
Temperature range	+5°C to +60°C	+5°C to +60°C	+5°C to +60°C	+5°C to +60°C	+5°C to +60°C
Cylinder material	Steel	Steel	Steel	Steel	Aluminium
Pressuring gas	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen
Dimensions (HxDmm)	664x170	522x170	380x110	320x85	300x65
MED approved	-	-	-	-	-
Weight	14.5kg	10.5kg	3.95kg	2.55kg	0.75kg
Battery capacity (Wh)	750 to 1000	350 to 750	150 to 350	50 to 150	up to 50

*Aqueous Vermiculite Dispersion

Bull Products Ltd
Beacon House, 4 Beacon Road
Rotherwas, Hereford HR2 6JF

Registered in England & Wales
Registered Number 8587906
VAT Number 873 5255 05

01432 371 170
sales@bullproducts.co.uk
www.bullproducts.co.uk

 **PROTECTABULL**
BY BULL PRODUCTS
Securing your safety